


Built to Last!

WUKO

WUKO Seam Hammer 1002B

Power tool for closing pre-fabricated standing seams.



Seam height	30 mm (1.2 in)
Sheet metal thickness:	
Galvanized steel	1.00–1.50 mm (0.039–0.059 in)
Aluminum	1.00–2.00 mm (0.039–0.079 in)
Stainless steel	1.00–1.25 mm (0.039–0.049 in)
Working speed	4–6 m/min (13–19 ft/min)
Standard voltage	230 V/120 V
Weight	4.5 kg (10.3 lbs)




WUKO Seam Closer 1003A

Closing of an offset to a standing seam on straight and round [min. radius 80 mm (3 in)] work pieces.

Accessories

Special jaws for a seam height of 3–6 mm (0.12–0.24 in)




Standard seam height	5–12 mm (0.20–0.47 in)
Max. sheet metal thickness:	
Galvanized steel	1.00 mm (0.039 in)
Stainless steel	0.60 mm (0.024 in)
Working speed	4–6 m/min (13–19 ft/min)
Standard voltage	230 V/120 V
Weight	3.75 kg (8.3 lbs)



WUKO Seam Closer 1003B

Closing of an offset to a standing seam on straight and round [min. radius 150 mm (6 in)] work pieces.




Seam height	6–14 mm (0.24–0.55 in)
Sheet metal thickness:	
Galvanized steel	1.00–1.50 mm (0.039–0.059 in)
Aluminum	1.00–2.00 mm (0.039–0.079 in)
Stainless steel	1.00–1.25 mm (0.039–0.049 in)
Working speed	4–6 m/min (13–19 ft/min)
Standard voltage	230 V/120 V
Weight	4.5 kg (10.3 lbs)



WUKO Pittsburgh Lock Closer 1004

Closing of Pittsburgh locks on straight work pieces as well as on outer and inner radii [min. 150 mm (6 in)]. Available for 3 different pocket depths: 5/16, 3/8 or 1/2 in.



Max. sheet metal thickness:	
Galvanized steel	1.20 mm (0.047 in)
Working speed	4–6 m/min (13–19 ft/min)
Standard voltage	230 V/120 V
Weight	3.85 kg (8.5 lbs)

